

ATH Cross Lift® 40 OGA

Product Images



Description

- High-quality and robust hydraulic drive platform scissor lift with minimal maintenance requirements
- Powerful hydraulic unit with load-dependent lowering speed controller
- Suitable installation on-ground with inclusive Kit for surface mounting
- With recesses for turning plates in the front and mechanically lockable sliding plates in the back, free-wheel lift (loading capacity: 4 t, lifting height: 450 mm), including rails for the optional rolling bridge jack, pluggable platforms-connections beams, incl. metal protections covers and switch for the optional 24V LED Lighting.
- Pneumatic unlocking of the safety locks, CE-Stop and acoustic signal through lowering
- Emergency lowering device for lowering in case of power failure, monitoring of safety synchronization by light barrier.
- Ideally suited for inspection, wheel alignment, repairing jobs and testing stations for driver assistance systems

Additional Information

Coleur	Anthrazit / Noir
Capacite de levage	4.000 kg
Hauteur de levee maxi	2.160 mm
Conduire en hauteur	295 mm
Longueur des chemins	4.230 mm
Largeur des chemins	600 mm
Puissance d'entraînement	3,5 kW
Temps monte / descente	ca. 70 s
Tension	3x 400V / C16A
Dalle beton	min. C20/25 5.500 x 3.000 x 200 mm

